

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

1. A method of reusing a photographic processing waste solution, comprising:

preparing a solidified matter from the photographic processing waste solution by a dry-solidification according to a thin film concentration method without removing ingredients accumulated during a photographic processing;

forming the solidified matter into granules; and

reusing the granules as a solid photographic processing agent.

2. The method as described in claim 1, which further comprises gathering waste solutions discharged in individual steps of photographic processing; and mixing the gathered waste solutions without removing ingredients accumulated in the individual steps.

3. The method as described in claim 1, which further comprises adding a chemical consumed during the photographic processing.

4. The method as described in claim 1, wherein the photographic processing waste solution is a waste solution

generated by a color paper processing.

5. The method as described in claim 1, wherein the solidified matter is prepared from the photographic processing waste solution by a dry-solidification according to a thin film concentration method at a temperature of 80°C or below.

6. The method as described in claim 1, wherein the solidified matter is prepared from the photographic processing waste solution by a dry-solidification according to a thin film concentration method at a temperature of 80°C or below under a reduced pressure.

7. The method as described in claim 1, wherein the solidified matter is prepared from the photographic processing waste solution by a dry-solidification according to a thin film concentration method without removing at least silver accumulated during the photographic processing.

8. The method as described in claim 1, wherein a reuse rate is from 70% to 90%, in which the reuse rate means a rate by weight of the amount of the solid matter obtained from the photographic waste solutions and reused

as a replenishing agent to the total amount by weight of the solid matter obtained from the photographic waste solutions.

9. The method as described in claim 1, which further comprises: recovering water vapor produced at the time of the dry-solidification of the photographic waste solutions; and liquefying the water vapor to utilize the water as the water for diluting the bleach-fix processing solution or the water of the rinsing bath.

10. The method as described in claim 1, wherein the photographic processing waste solution is a mixture of processing waste solutions discharged in a development-processing step, a bleach-fix processing step and at least one of a rinse and stabilization-processing step.

11. A solid photographic replenishing agent produced in accordance with the method as described in claim 1.